## (19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 28 April 2005 (28.04.2005)

**PCT** 

## (10) International Publication Number WO 2005/038727 A1

(51) International Patent Classification7:

G07C 9/00

(21) International Application Number:

PCT/SE2004/001448

(22) International Filing Date: 12 October 2004 (12.10.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0302733-1

16 October 2003 (16.10.2003) SE

(71) Applicant (for all designated States except US): SOLID AB [SE/SE]; Sjöviksbacken 24, plan 8, S-117 43 Stockholm (SE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): THORSEN, Hans [SE/SE]; Korsfararvägen 18, S-181 40 Lidingö (SE).

(74) Agents: ESTREEN, Lars et al.; Kransell & Wennborg AB, Box 27834, S-115 93 Stockholm (SE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

## Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A LOCK SYSTEM AND A METHOD OF CONFIGURING A LOCK SYSTEM.



(57) Abstract: A lock system (100) is owned by a lock system owner and comprises a management computer (110) connected to a plurality of door access control units (120). A method of configuring this system comprises the following steps: installing in the door access control units a first certificate issued by a manufacturer (10) of the lock system; providing at the management computer (110) a second certificate issued by the lock system owner and signed by the manufacturer; transmitting from the management computer to a first door access control unit of the door access units the signed second certificate together with a symmetric encryption key used by the lock system owner; installing by means of asymmetric encryption the second certificate at the first door access control unit after checking the authenticity of the signed second certificate; and establishing of symmetric encryption communication between the management computer and the first door access unit. Simple yet secure installation of the lock system is thereby achieved.

